



NOTES

Street nameplates are to be provided and sited on either side of the junction and facing the exit from the connecting road. Street and footpath nameplates are to be provided and erected to the requirements before any dwellings are occupied. These are to conform to the following specification unless otherwise agreed:-

- A) 87.5 Kindersley characters semi-sheared black on white background.
- B) 12.5mm black border
- C) The plate to be 12 gauge aluminium 225mm deep with one line of lettering or 375mm deep for two lines. the width not exceeding 1.3m.
- D) The plate to be mounted in a frame before delivery, mounting to be with galvanised pop rivets.
- E) The nameplates are to be positioned so the top is no less than 700mm or more than 900mm above finished carriageway level.
- F) Where necessary, the nameplate shall incorporate a sign indicating 'NO THROUGH ROAD' in accordance with diagram 816.1 of The Traffic Signs Regulations and General Directions 2002.
- G) The nameplates shall incorporate the names of roads leading from the main access road as required.
- H) For conservation and rural areas please contact the Engineer.
- I) Concrete footings 250mm dia x 300mm deep starting 150mm below ground level



PLANNING, HOUSING & ENVIRONMENTAL HEALTH

Chief Engineer
Mike O'Brien BSc(Hons) C Eng MICE
 Gibson Building
 Gibson Drive
 Kings Hill
 West Malling
 Kent ME19 4LZ
 Tel: 01732 844522 Fax: 01732 876317

Project Title
Standard Details

Drawing Title
Street Nameplate

Drawn SM	Checked	Date 11/01/07
Scale		
Drawing No. DD/391/1		Rev A